



Marine Slings

It's that time again...

Check your slings, and replace or re certify!


Nylon Marine slings (MS) are lightweight and easy to use. They will not scratch or abuse the most delicate hull.

SINGLE PLY		
Code	Width in.	Basket Pounds
MS1-903	3	9,400
MS1-904	4	12,400
MS1-906	6	18,600
MS1-908	8	23,500
MS1-910	10	29,400
MS1-912	12	35,300


DOUBLE PLY		
Code	Width in.	Basket Pounds
MS2-903	3	17,600
MS2-904	4	22,000
MS2-906	6	33,000
MS2-908	8	45,500
MS2-910	10	56,800
MS2-912	12	68,200

WARNING: The maximum loads shown are applicable for products in new conditions.


Do not exceed maximum rated capacities.



Extra eyes are available in tapered fabric or for use with hardware. Allows a single sling to adjust to different overall lengths.



Quick disconnects allow for easy removal and installation of slings. Protective flap included.



Keel pad is fastened to the sling at the centre to protect the sling from wear at the greatest load point.




Lead weights keeps slings under water. Allows easier positioning of slings under boat.

Re-Certification:

Send in for re-certification: Sling, hooks, ropes, chain hoists, hoist rings, hardware. With all proof tests, and destruction tests, you will receive a printed certificate.

Ben-Mor has a **ROBERTS 350,000 lbs, 60 FT** horizontal test bed. We can offer in-house testing & certification. All slings tested come complete with the proof test certificate, and are logged on-line with EasyTrack.



1 800 423-4423

690, Bayview Dr. Barrie, Ontario, Canada, L4N 9A6

sales@ben-mor.com

ben-mor.com





Docking Accessories...

**Screw Pin
anchor shackles**



Brown Pin®

**Wire rope
clips Brown**



Brown Pin®



Cable assemblies



Galvanized cable

1 800 423-4423

690, Bayview Dr. Barrie, Ontario, Canada, L4N 9A6

sales@ben-mor.com

ben-mor.com